

*** Patented MAX In-Wall™
Technical Specifications**

MAX In-Wall™ B&O



The **MAX In-Wall™ B&O Module** provides clean AC power specifically for Bang & Olufsen systems, eliminating potential grounding problems by creating an Isolated Ground Reference™ for the remote equipment. Integrated signal line protection is included to protect B&O's proprietary MasterLink and PowerLink circuits.

GENERAL

Product NameMAX In-Wall™ B&O
Part NumberMIW-B&O (MIW0100)
Retail Price\$99.95
ApplicationB&O Speaker & Home Theater Systems
Power CordNO (hard-wired)

AC CIRCUIT

AC Outlets, Total1
AC120V, 60Hz, 15A
Energy Dissipation675 joules (8x20ms)
Current Capacity26,000 Amps (8x20ms)
SignalPerfect Protection .YES (1 ea, MasterLink & PowerLink)
UL® / cUL Listed (1449 2nd Edition)YES
UL 1449 Suppression Voltage400V L-N, L-G, N-G

MASTERLINK SPECIFICATIONS

Input ConnectorPunch-down terminals
Output ConnectorMasterLink
Pins Connected/Protected1-3, 11-16
Limiting Voltage15V
Insertion Loss-0.6dB, 1Hz-50KHz
Crosstalk-81dB, 1Hz-50KHz

POWERLINK SPECIFICATIONS

Input Connector8-position terminal Block
Output Connector8-pin DIN
Pins Connected/ProtectedALL

PRODUCT WARRANTY

Product Warranty3 years

ORDERING INFORMATION

Unit Dimensions4.38"W x 3.81"L x 4.38"H
Individual Unit UPC0 50616 00729 0
Packaging TypeRetail Box
Packaging Dimensions4.75"W x 4.00"L x 4.75"H
Unit Weight (packaged)1.00 lbs.
Units per Inner Pack3
Inner Pack UPC3 00 50616 00729 1
Inner Pack Dimensions14.0"W x 5.50"L x 5.19"H
Inner Pack Weight4.45 lbs.
Units per Master Carton12 (4 Inner Packs)
Master Carton UPC5 00 50616 00729 5
Master Carton Dimensions 14.75"W x 11.25"D x 10.75"H
Master Carton Weight18.60 lbs.