



MAX[®] 4400-20A

Component Style, 20Amp Power Distribution / Protection

MAX[®] 4400-20A **\$299 SRP**



Optional Silver Front Bezel Available

- 20 Amp Current Capacity** - receptacles accept either 15 or 20 Amp equipment plugs for installation flexibility.
- Inductorless Noise Filtration** - provides clean, capacitive filtered power to amplifiers without current limiting components (inductors) which impede performance.
- One Front Panel Convenience Outlet** - for temporary power connections.
- Four Always-On Outlets** - for equipment that requires continuous power.
- Four Switched Outlets** - controlled by either the front panel switch or DC voltage trigger. A Turn-On delay switch provides a 0 or 10 second delay for switched outlets.
- DC Voltage Trigger** - a standard 3.5mm mini-plug jack allows external control of startup/shutdown sequencing.
- SurgeGate Plus[™] Circuitry** - a Power monitoring system that acts as a gate to prevent unsafe voltages from damaging sensitive electronic equipment. It automatically detects a prolonged over or undervoltage condition and disconnects the power to equipment, then reconnects it when the power returns to a safe level.
- Grounding Lug** - provides a common grounding point for equipment with separate ground.
- Optional Silver Front Bezel Available** - (Part# BEZ4400-S) \$39.00 SRP

AC SPECIFICATIONS	
Line Voltage:	120VAC, 50/60 Hz
Maximum Current Capacity:	20 Amps
Protection Modes	L-N, L-G, N-G
UL 1449 Suppression Rating:	330V
Joule Rating:	1650
Peak Impulse Current:	52,000 Amps
Initial Clamping Level:	141 RMS / 200 Peak
Response Time:	<1ns
EMI/RFI Noise Filtration:	50dB (100KHz - 1MHz)
Catastrophic Surge Circuit:	Yes
Thermal Fusing:	Yes
Overvoltage Shutoff:	147VAC +/- 8VAC
Undervoltage Shutoff:	84VAC +/- 6VAC

Includes Rack-Mounting Brackets



DC TRIGGER SPECIFICATIONS	
Connection:	3.5mm mini-plug
Voltage and Polarity:	5-30VDC, bi-directional
Current Requirement:	<10mA

L488 Rev A
7/03



PANAMAX
The Surge Protection Specialist

www.panamax.com

(800) 472-5555 (707) 283-5900

1690 Corporate Circle, Petaluma, CA 94954