

# MIW-XT

## MAX<sup>®</sup> IN WALL<sup>™</sup> POWER MANAGEMENT EXTENDER SYSTEM

**M** IW-XT extends noise free, safe power from Panamax / Furman Power Management components to remote panel displays, ceiling mounted video projectors and powered sub-woofers. Discreetly hides behind electronic equipment for a neat, clean, code compliant and professional installation.

- Ultra-thin profile can allow equipment to hang less than one inch from the wall.
- EMI/RFI noise filtration built into outlet receptacle.
- Power and signal lines are *hidden in the wall behind panel displays* for a clean, tidy and professional installation.
- Extend Connected Equipment Policy to remote equipment when used with Panamax/Furman Power Management components.
- Accommodates optional MIW Signal Line Modules (sold separately, contact Panamax or Furman).
- CSA Certified for code compliant installations.
- 3 Year Product Warranty

Installation requires use of an **outlet box or boxes that are NOT provided with the product**. Product has been tested thoroughly to be compatible with the following outlet boxes:

	NEW WORK	OLD WORK
Plastic:	Carlton SC200DV	Carlton B114R
Metal:	Raco 8355	Raco 508 (hardware removed)


### MODEL: MIW-XT

Elegant, nickel plated steel faceplates with brushed metal finish.




Signal bay on both INLET and OUTLET provides a wide variety of optional installation solutions by using:


#### Decora<sup>®</sup> Adapters




#### Pass-Through Inserts



#### Keystone 2-Port Adapter



#### MIW Signal Line Modules\*




\*MIW modules sold separately



By Panamax-Furman  
**PFP** Power

L611-PFP REV. F

## FEATURES



Pass-through inserts feature adjustable depth settings and can accommodate grommett (shown above) or Keystone 2-port adapter.



Clip secures plug to inlet faceplate.

MIW-XT inlet faceplate



6 ft. IEC / NEMA Inlet Faceplate power cord



MIW-XT outlet faceplate

Plug clip

Flat plug adapter cord

6 Wire nuts

Keystone 2-Port Adapters


Decora Adapters can accommodate 6-port insert (insert not included)

Rear view of faceplate assembly.



Ultra thin profile of flat plug can allow equipment to hang less than one inch from the wall.

## TYPICAL APPLICATION



\*Signal Bay can also accommodate MIW Signal Line Modules (sold separately).

## TECHNICAL SPECIFICATIONS

### AC CIRCUIT

AC Outlets, Total.....1  
Line Voltage.....120V, 60Hz  
Total Current Capacity.....15A

### IEC POWER INLET CORD

Length.....6 ft.  
Connectors.....IEC 320-C13 and NEMA 5-15

### FLAT PLUG AC POWER CORD

Length.....11 inches  
Connectors.....NEMA 5-15P and NEMA 5-15R

### PRODUCT DIMENSIONS FOR INLET & OUTLET\*

Faceplates.....4.75 in. Width X 4.75 in. Height X 0.25 in. Depth  
Assembly Behind Faceplate.....3 in. Depth  
\* Basic Dimensions Only. These do not include cords, plugs, module cable connectors, cables, wires, etc.

### POWER INLET FACEPLATE

AC Connector.....IEC 320 C14  
Signal Line Protection not included, modules sold separately\*

### POWER OUTLET FACEPLATE

AC Connector.....NEMA 5-15  
Noise Filtration.....Level 1  
Signal Line Protection not included, modules sold separately\*

### GENERAL

Product Warranty.....3 years

\*Contact Panamax or Furman for signal line protection modules.

Design and specifications subject to change without notice due to product improvement.

### SHIPPING DIMENSIONS, WEIGHTS AND UPC CODES

Single Pack Dimensions.....7.25"W x 5"D x 7"H  
Single Pack Weight.....4 lbs.  
Single Unit UPC.....0 50616 00848 8  
Master Pack Dimensions.....15"W x 10.5" D x 7.5" H  
Master Pack Qty.....4 Kits  
Master Pack Weight.....17 lbs.  
Master Pack UPC.....5 00 50616 00848 3

Model: MIW-XT

L611-PFP REV. F



1690 Corporate Circle, Petaluma, CA 94954 800-472-5555 • 707-283-5900