

*** Patented MAX In-Wall™
Technical Specifications**

MAX In-Wall™ DATA Module



The **MAX In-Wall™ DATA Module** inserts into any **MIW-POWER** unit to protect against surges on both signal and power lines; thus, eliminating potential grounding problems by creating an Isolated Ground Reference for the remote equipment. The **MIW-DATA** accepts RS-232 and 10/100bT Ethernet signal lines running between source components and remote equipment. Devices connect to standard RJ-45 jacks on the face of the module. Ethernet cabling inside the wall connects to an RJ-45 jack. RS-232 cabling inside the wall connects to a screw terminal block. Protect multiple signal lines with one module and the installation flexibility the **MIW-DATA** delivers.

GENERAL

Product NameMAX In-Wall™ Data Module
Part NumberMIW-Data
Retail Price\$59.95
Application	Home Theater Systems & Computer Networks
Power CordNO
UL® / cUL Listed (1449 2nd Edition)YES

ETHERNET

Protection ModePins 1,2,3,6 to Ground
Clamping8-10 VDC Limiting
Input/OutputRJ45 Input & Output

RS-232

Protection ModePins 1-8 to Ground
Current15-24 VDC Limiting
InputTerminal Block Input
OutputRJ45

PRODUCT WARRANTY

Product Warranty3 years
------------------------	----------

ORDERING INFORMATION

Unit Dimensions1.19"W x 5.50"L x 2.88"H
Individual Unit UPC0 50616 00741 2
Packaging TypeRetail Box
Packaging Dimensions2.95"W x 1.35"L x 7.85"H
Unit Weight (packaged)0.6 lbs.
Units per Inner Pack6
Inner Pack UPC3 00 50616 00741 3
Inner Pack Dimensions6.50"W x 4.80"L x 8.40"H
Inner Pack Weight4.0 lbs.
Units per Master Carton24 (4 Inner Packs)
Master Carton UPC5 00 50616 00741 7
Master Carton Dimensions9.90"W x 13.30"D x 8.70"H
Master Carton Weight17 lbs.

Design and specifications for all MAX IN-WALL™ modules are subject to change without notice due to product improvement.

©2004 Panamax, MAX, MAX In-Wall, and the Panamax logo are registered US trademarks of Panamax.